

[Previous Doc](#)   [Next Doc](#)   [Go to Doc#](#)  
[First Hit](#)

☐ [Generate Collection](#)

L12: Entry 27 of 32

File: JPAB

Sep 6, 2002

PUB-NO: JP02002250353A  
DOCUMENT-IDENTIFIER: JP 2002250353 A  
TITLE: ROLLING BEARING

PUBN-DATE: September 6, 2002

INVENTOR-INFORMATION:

NAME

COUNTRY

DENPO, KOUTETSU

YATANI, KOICHI

NAKA, MICHIHARU

SHODA, TORU

KOIZUMI, HIDEKI

INT-CL (IPC): [F16 C 33/66](#); [C10 M 107/38](#); [C10 M 107/50](#); [C10 M 113/10](#); [C10 M 113/12](#);  
[C10 M 119/22](#); [C10 M 125/00](#); [C10 M 125/02](#); [C10 M 125/08](#); [C10 M 125/10](#); [C10 M 125/20](#);  
[C10 M 125/26](#); [C10 M 125/30](#); [C10 M 169/00](#)

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a rolling bearing having excellent electric conductivity even at a high temperature.

SOLUTION: In a ball bearing 10 provided with an outer ring 11, an inner ring 12, a plurality of balls 13 rollably arranged between both rings 11 and 12, and electrical conductive grease G filled into a space 16 formed between both rings 11 and 12 with the balls 13 set therein, the electric conductive grease G is composed of base oil, a thickener composed of a fluorine compound, and 0.2 to 10 mass % carbon black.

COPYRIGHT: (C)2002,JPO

[Previous Doc](#)   [Next Doc](#)   [Go to Doc#](#)